



## **MATERIAL SAFETY DATA SHEET**

Print date: 08-Oct-2008 Revision Number: 1 Revision date: 08-Oct-2008

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Trade Name: LEXAN\*

Product Name: LEXAN\* Thermoclick\*

**Product Description:** Polycarbonate (CAS# 25971-63-5)

Recommended use: May be used as received, processed or thermoformed to produce

other articles, or as a component of other industrial products.

Company: SABIC Innovative Plastics B.V.

Plasticslaan 1 P.O. Box 117

4600 AC Bergen op Zoom

The Netherlands

Emergency Telephone Number: +31(0)164-292911 (24/24) Bergen op Zoom

E-mail: webinquiries@sabic-ip.com

### 2. HAZARDS IDENTIFICATION

**Skin Contact:** Not likely to cause irritation.

**Eye Contact:** No eye irritation.

Inhalation: Inhalation unlikely due to physical form.

**Ingestion:** Ingestion not likely due to physical form.

Other Information: Hazardous fumes can also occur in post-processing operations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Not a hazardous substance or preparation according to EC-directives 67/548/EEC or 99/45/EC.

# 4. FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. If symptoms persist, call a physician.

Skin Contact: Not applicable.

Eye Contact: Not applicable.

**Ingestion:** No hazards which require special first aid measures.

Precautions: Cool molten product on skin with plenty of water. Do not remove

solidified product. Do not peel polymer from the skin.

### 5. FIRE-FIGHTING MEASURES

**Autoignition Temperature:** 630°C (1166°F), estimated.

**Explosive Limits** 

upper:Not applicablelower:Not applicable

Suitable Extinguishing Media: Water spray mist or foam.

Extinguishing Media not be used for Safety Reasons: Carbon dioxide and dry chemical are not recommended because

their lack of cooling capacity may permit re-ignition.

**Hazardous decomposition products:** Fire will produce dense black smoke containing hazardous

combustion products, carbon oxides, hydrocarbons fragments.

Special Protective Equipment for Firefighters: In the event of fire, wear self-contained breathing apparatus (NEN-

EN137).

Specific Hazards: Take precautionary measures against static discharges. Thermal

decomposition can lead to release of irritating gases and vapors.

### **6. ACCIDENTAL RELEASE MEASURES**

Clean up: Sweep up and shovel into suitable containers for disposal.

Personal Precautions: See section 8.

Environmental Precautions: Should not be released into the environment.

### 7. HANDLING AND STORAGE

Handle in accordance with good industrial hygiene and safety

practice. Provide for appropriate exhaust ventilation and dust

collection at machinery.

Storage: Keep tightly closed in a dry and cool place. Keep away from heat

and sources of ignition.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Measures to Reduce Exposure: Handle in accordance with good industrial hygiene and safety

practice.

**Hand Protection:** Protective gloves, NEN-EN 374. **Eye Protection:** Not required under normal use.

Respiratory Protection: In the case of hazardous fumes, wear self contained breathing

apparatus In case of insufficient ventilation wear suitable respiratory

equipment (NEN-EN149).

Skin and Body Protection: Long sleeved clothing (NEN-EN 340-369-465).

**Hygiene Measures:** Do not eat, drink or smoke at work.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:SolidAppearance:SheetsColor:VariousOdor:None

Melting point/range: Various

**Autoignition Temperature:** 630°C (1166°F) estimated

Vapor Pressure: Negligible

Water Solubility: Insoluble Evaporation Rate: Negligible

Specific gravity: >1; (water =1)
VOC content(%): Negligible

**Explosive Limits** 

upper:Not applicablelower:Not applicable

### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions. Hazardous polymerisation does not

occur.

Conditions to Avoid: Do not expose to temperatures above 200 °C. Heating can release

hazardous gases.

**Hazardous Decomposition Products:** Traces of phenol, alkylphenols, diarylcarbonates, hydrocarbons.

11. TOXICOLOGICAL INFORMATION	
LD50/oral/rat:	5000 ma/ka
	>5000 mg/kg
LD50/dermal/rabbit:	>2000 mg/kg
Subchronic Toxicity:	No data available
Primary Irritation:	Substance does not generally irritate and is only mildly irritating to the skin
Remarks:	The toxicological data has been taken from products of similar composition
12. ECOLOGICAL INFORMATION	
Ecotoxicity Effects:	None expected for this article.
Other Information:	Ecological damages are not known or expected under normal use.
13. DISPOSAL CONSIDERATIONS	
101 2101 3371	
Waste from residues / unused products:	Where possible recycling is preferred to disposal or incineration. Dispose of in accordance with local regulations.
EWC waste disposal no:	702 - waste from the mfsu of plastics, synthetic rubber and manmade fibres
14. TRANSPORT INFORMATION	
Transport Classification:	Not regulated as hazardous for shipment, unless noted below, under current transportation guidelines.
ADR/RID/ADNR	
IMDG	
ICAO	
IATA-DGR	
15. REGULATORY INFORMATION	
Not a hazardous substance or preparation according to EC-directives 67/548/EEC or 99/45/EC.	
R -phrase(s)	
S -phrase(s)	

## **16. OTHER INFORMATION**

#### Text of R Phrases mentioned in Section 3

LEXAN\* is a registered trademark of SABIC Innovative Plastics BV

#### Prepared by:

Product Stewardship & Toxicology.

This publication provides information and guidelines for safe handling and processing of SABIC Innovative Plastics' products and is based on currently available experience and knowledge. It is not designed as a comprehensive product performance data sheet, nor as a guide to application possibilities of our materials.

Users should follow all applicable local regulations governing Health and Safety at work, and are requested to pass this publication on to all relevant employees and customers.

**End of Material Safety Data Sheet** 

Product Name: **LEXAN\* Thermoclick\*** Page 5 of 5 Revision date: 08-Oct-2008